



Kvaser Leaf Professional LS

EAN: 73-30130-00261-6

Kvaser Leaf Professional HS是一款通道CAN和LIN的USB品。提供接任意几品至一台PC。通MagiSync™功能自同步客提供方便同也适合多通道使用。品可配支持高速,低速和 CAN及LIN

主要特性:

- 易快速安
- 使用准USB接口
- 支持11位(CAN2.0A) 准和29位(CAN2.0B)展
- Kvaser家利, MagiSync戳同步功能
- 每秒20000文的理能力
- 文的精准度可1微妙
- 文自送功能
- 支持
- 卓越的能力
- 分析工具提供安模式
- 低耗,良好的EMC性能

Kvaser
Aminogatan 25 A SE 431 53 Mndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



- 均使用聚氨酯复合材料, 适合各极端的工作境
- 隔离, 保CAN芯片和硬件
- 提供免CANKing分析件, 支持Kvaser CANlib件包
- 配110cm(44in)USB接口×30cm(12in)CAN 配9D-Sub接口,根据CiA-DS102配置Pin



TECHNICAL DATA - KVASER LEAF PROFESSIONAL LS	
PC INTERFACE	USB
CASING MATERIAL	玻璃增PA6
NETWORK CHANNEL(S)	1 x CAN LS
CIRCUIT BOARD	No
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
CAN FD	No
SILENT MODE	Yes
OPERATING TEMPERATURE RANGE (C)	-40 °C to +85 °C
# OF CAN CHANNELS	1
IP CLASS	IP40
SOUND	Yes
GALVANIC ISOLATION	Yes
API, FREE	Kvaser API, J2534, RP1210
CERTIFICATIONS	CE, RoHS
ON-BOARD TX BUFFER	Yes
EMBEDDED SCRIPT	No
PROMOTIONAL_TEXT	适用于低速容 CAN 的通道 CAN USB的适配器(ISO 11898-3)。
ERROR FRAME GENERATION	Yes
API, LICENCED	
MSGRATE RX MAX	2500
PRODUCT GROUPS	Leaf
STATUS	Obsolete
MINIMUM BITRATE (KBPS)	5
CONNECTOR	DSUB 9
HEIGHT (MM)	20
ON-BOARD RX BUFFER	Yes
WEIGHT (G)	100.0

Kvaser
Aminogatan 25 A SE 431 53 Mndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



Kvaser Leaf Professional LS

ON-BOARD BUFFER	Yes
CURRENT CONSUMPTION	常值70mA
RUGGED	No
CLOCK SYNC	Yes
MSGRATE TX MAX	2500
WIDTH (MM)	25
LENGTH (MM)	100
ERROR COUNTERS READING	Yes
MAXIMUM BITRATE (KBPS)	125
TIMESTAMP RESOLUTION (US)	1
ERROR FRAME DETECTION	Yes

The information herein is subject to change without notice