



### Kvaser OBD II Extension Cable 15m

EAN: 73-30130-00349-1

Kvaser's OBD II Extension Cable is a highly durable extension cable of 15 metres in length with male to female [OBD II](#) connectors. The cable is made of high quality thermoplastic rubber to ensure excellent flexibility and resilience. All pins are connected.

#### Major Features

- Molded [OBD II \(SAE J1962\)](#) male connector, Type B (24 Volt).
- Molded OBD II (SAE J1962) female connector, Type B (24 Volt).
- Made of durable thermoplastic rubber.
- Gold plated pins on OBDII connectors for extra reliable contact.
- Termination is built in with a 120 Ohm terminating resistor.
- Available in other cable lengths.
- RoHS compliant.
- This cable can save wear and tear on your CAN interface's OBD2 connector.



## Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

## Support

- Free Technical Support on all products available by contacting [support@kvaser.com](mailto:support@kvaser.com).

TECHNICAL DATA - KVASER OBD II EXTENSION CABLE 15M

OPERATING SYSTEM	Win 10, Linux, Win Vista, Win 8, Win 7, Win XP
HEIGHT (MM)	N/A
MSGRATE TX MAX	N/A
API, FREE	N/A
API, LICENCED	
SILENT MODE	N/A
ON-BOARD RX BUFFER	No
ON-BOARD BUFFER	N/A
CLOCK SYNC	No
WEIGHT (G)	1400.0
SILENT MODE	No
IP CLASS	
STATUS	Active
MINIMUM BITRATE (KBPS)	N/A
PRODUCT GROUPS	Cable
# OF CAN CHANNELS	1
LENGTH (MM)	15000
CONNECTOR	N/A
CAN FD	No
HEIGHT (MM)	N/A
LENGTH (MM)	15000
PRICE EXAMPLE	0.00 to 99999999.00
PC INTERFACE	Cable
MAXIMUM BITRATE (KBPS)	N/A
API, FREE	
ERROR FRAME DETECTION	No
ON-BOARD TX BUFFER	No

SOUND	No
ERROR FRAME GENERATION	N/A
CERTIFICATIONS	CE,RoHS
# OF CAN CHANNELS	1
DATABASE DBC SUPPORT	No
MAGISYNC	N/A
PC INTERFACE	Cable
API, LICENCED	None
WEIGHT (G)	1400.0
CB BOARD	No
MSGRATE RX MAX	N/A
CB BOARD	No
MINIMUM BITRATE (KBPS)	N/A
EMBEDDED SCRIPT	No
WIDTH (MM)	N/A
CURRENT CONSUMPTION	N/A
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
ERROR FRAME DETECTION	N/A
CERTIFICATIONS	CE,RoHS
MAXIMUM BITRATE (KBPS)	N/A
SOUND	N/A
ON-BOARD BUFFER	No
STATUS	Active
ON-BOARD TX BUFFER	N/A
CONNECTOR	N/A
PRODUCT GROUPS	Cable
RUGGED	No
WIDTH (MM)	N/A

MSGRATE TX MAX	N/A
CLOCK SYNC	N/A
TIMESTAMP RESOLUTION (US)	N/A
CURRENT CONSUMPTION	
CASING MATERIAL	
OPERATING SYSTEM	Linux,Win Vista,Win 10,Win 8,Win 7,Win XP
CAN FD	No
CASING MATERIAL	Durable thermoplastic rubber
ERROR COUNTERS READING	No
PLAY BACK LOG FILE	No
ERROR FRAME GENERATION	No
GALVANIC ISOLATION	No
GALVANIC ISOLATION	N/A
ON-BOARD RX BUFFER	N/A
NETWORK CHANNEL(S)	
OPERATING TEMPERATURE RANGE (C)	-100.00 to 250.00
RUGGED	No
MSGRATE RX MAX	N/A
EMBEDDED SCRIPT	No
TIMESTAMP RESOLUTION (US)	N/A
ERROR COUNTERS READING	N/A
IP CLASS	N/A
NETWORK CHANNEL(S)	

The information herein is subject to change without notice