



### Kvaser Q

EAN: 73-30130-00199-2

Q是接Kvaser PCicanx 4xHS和Kvaser PCican 4xHS板的0.3米（0.98英尺）的适配器。1DSUB公接接PCican板，而4DSUB公接接CAN。

#### 主要特性

- Kvaser PCicanx 4xHS和Kvaser PCican 4xHS板的适配器。
- 1模25含翼形螺DSUB公接接CAN接口板。
- 4模9含翼形螺DSUB公接接CAN。
- 提供3米低Q（品00340-8）防止有毒和腐性气体保人和。

#### 保修

- 2年保修。情一般性款和政策。

#### 助

- 系support@kvaser.com取免品技支持。



Kvaser Q

Kvaser  
Aminogatan 25 A SE 431 53 Mndal SWEDEN  
Kvaser Europe AB  
Telephone: +46 31 886344  
Email: [sales@kvaser.com](mailto:sales@kvaser.com)  
<https://www.kvaser.com/>

© 2020 Kvaser



## TECHNICAL DATA - KVASER Q

SOUND	No
STATUS	Active
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
ERROR COUNTERS READING	N/A
NETWORK CHANNEL(S)	
CASING MATERIAL	Durable thermoplastic rubber
CONNECTOR	N/A
ERROR COUNTERS READING	No
GALVANIC ISOLATION	N/A
CAN FD	No
# OF CAN CHANNELS	4
MAXIMUM BITRATE (KBPS)	N/A
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
LENGTH (MM)	300
MINIMUM BITRATE (KBPS)	N/A
ERROR FRAME GENERATION	No
SILENT MODE	N/A
ON-BOARD RX BUFFER	N/A
ERROR FRAME GENERATION	N/A
MAXIMUM BITRATE (KBPS)	N/A
PC INTERFACE	Cable
WEIGHT (G)	200.0
ON-BOARD RX BUFFER	No
PC INTERFACE	Cable
API, LICENCED	None
API, FREE	N/A
WEIGHT (G)	200.0
PRODUCT GROUPS	Cable



ON-BOARD TX BUFFER	No
CERTIFICATIONS	CE,RoHS
CURRENT CONSUMPTION	N/A
CB BOARD	No
CLOCK SYNC	No
PRODUCT GROUPS	Cable
ERROR FRAME DETECTION	N/A
EMBEDDED SCRIPT	No
MSGRATE RX MAX	N/A
API, FREE	
PROMOTIONAL_TEXT	Adapter cable for the Kvaser PCICanx 4xHS and Kvaser PCICan 4xHS.
PROMOTIONAL_TEXT	Kvaser PCICanx 4xHS 和 Kvaser PCICan 4xHS 的器
ON-BOARD TX BUFFER	N/A
TIMESTAMP RESOLUTION (US)	N/A
LENGTH (MM)	300
RUGGED	No
HEIGHT (MM)	N/A
SOUND	N/A
EMBEDDED SCRIPT	No
MSGRATE TX MAX	N/A
CERTIFICATIONS	CE,RoHS
GALVANIC ISOLATION	No
ON-BOARD BUFFER	No
NETWORK CHANNEL(S)	
CURRENT CONSUMPTION	
CASING MATERIAL	耐用型塑性橡
IP CLASS	N/A
ERROR FRAME DETECTION	No



WIDTH (MM)	N/A
WIDTH (MM)	N/A
HEIGHT (MM)	N/A
MSGRATE RX MAX	N/A
TIMESTAMP RESOLUTION (US)	N/A
CLOCK SYNC	N/A
# OF CAN CHANNELS	4
CB BOARD	No
API, LICENCED	
RUGGED	No
IP CLASS	
MINIMUM BITRATE (KBPS)	N/A
SILENT MODE	No
CONNECTOR	N/A
STATUS	Active
DATABASE DBC SUPPORT	No
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
ON-BOARD BUFFER	N/A
MSGRATE TX MAX	N/A
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
CAN FD	No

The information herein is subject to change without notice