



Kvaser DRVcan Fi TnT

EAN: 73-30130-00406-1

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

- DRVcan 251 and DRVcan 1050 are for normal, high-speed ISO 11898 CAN bus systems.
- DRVcan Dnopto is also intended for normal, high-speed ISO 11898 CAN bus systems but is equipped with optocouplers.
- DRVcan 1053 and DRVcan 1054 are for fault-tolerant CAN buses (sometimes called "low-speed CAN")

Kvaser

Aminogatan 25 A SE 431 53 Mölndal SWEDEN Kvaser Europe AB Telephone: +46 31 886344 Email: sales@kvaser.com https://www.kvaser.com/



- DRVcan Fi employs optical fiber and is used for special applications.
 Different physical layers are supported through different product versions.
- DRVcan TnT is used with Truck and Trailers, ISO 11992-1
- DRVcan S is used with Single-Wire CAN (SAE J2411, GMLAN)
- DRVlin is used with the LIN bus. Please note that notnote that not all applications listed under Application Support for LAPcan/LAPcan II support the DRVlin.

N/A

No



TECHNICAL DATA - KVASER DRVCAN FI TNT	
CAN FD	No
PC INTERFACE	PCMCIA
CIRCUIT BOARD	No
OPERATING TEMPERATURE RANGE (C)	+0 °C to +55 °C
STATUS	Obsolete
ON-BOARD BUFFER	No
ERROR COUNTERS READING	Yes
SOUND	No
HEIGHT (MM)	N/A
ERROR FRAME DETECTION	Yes
WIDTH (MM)	N/A
SILENT MODE	Yes
MSGRATE TX MAX	5000
MAXIMUM BITRATE (KBPS)	250
INVENTORY	Call Us
WEIGHT (G)	50.0
API, LICENCED	None
GALVANIC ISOLATION	Yes
# OF CAN CHANNELS	1
CASING MATERIAL	PC-ABS
IP CLASS	IP40
EMBEDDED SCRIPT	No
CERTIFICATIONS	CE
API, FREE	N/A
DATABASE DBC SUPPORT	No

Kvaser Aminogatan 25 A SE 431 53 Mölndal SWEDEN Kvaser Europe AB Telephone: +46 31 886344 Email: sales@kvaser.com https://www.kvaser.com/

ON-BOARD TX BUFFER

ERROR FRAME GENERATION





RUGGED	No
CLOCK SYNC	N/A
LENGTH (MM)	500
NETWORK CHANNEL(S)	
CURRENT CONSUMPTION	N/A
CONNECTOR	N/A
PRODUCT GROUPS	
MINIMUM BITRATE (KBPS)	5
TIMESTAMP RESOLUTION (US)	N/A
ON-BOARD RX BUFFER	N/A
OPERATING SYSTEM	Win XP,Linux,Win 7,Win Vista,Win 10,Win 8
MSGRATE RX MAX	5000

The information herein is subject to change without notice