



Kvaser DRVcan Fi HS

EAN: 73-30130-00299-9

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

-

DRVcan 251 and DRVcan 1050 are for normal, high-speed ISO 11898 CAN bus systems.

-



DRVcan Dnopto is also intended for normal, high-speed ISO 11898 CAN bus systems but is equipped with optocouplers.

-

DRVcan 1053 and DRVcan 1054 are for fault-tolerant CAN buses (sometimes called "low-speed CAN")

-

DRVcan Fi employs **optical fiber** and is used for special applications. Different physical layers are supported through different product versions.

-

DRVcan TnT is used with Truck and Trailers, ISO 11992-1

-

DRVcan S is used with Single-Wire CAN (SAE J2411, GMLAN)

-

DRVlin is used with the LIN bus. Please note that notnote that not all applications listed under Application Support for LAPcan/LAPcan II support the DRVlin.



TECHNICAL DATA - KVASER DRVCAN FI HS

CURRENT CONSUMPTION	N/A
INVENTORY	Call Us
TIMESTAMP RESOLUTION (US)	N/A
MAXIMUM BITRATE (KBPS)	1000
ERROR FRAME DETECTION	Yes
SOUND	No
DATABASE DBC SUPPORT	No
MSGRATE TX MAX	8000
WIDTH (MM)	N/A
ON-BOARD BUFFER	No
SILENT MODE	Yes
CERTIFICATIONS	CE
ERROR COUNTERS READING	Yes
MSGRATE RX MAX	N/A
API, LICENCED	None
CONNECTOR	DSUB 9
NETWORK CHANNEL(S)	
CIRCUIT BOARD	No
LENGTH (MM)	500
GALVANIC ISOLATION	Yes
OPERATING TEMPERATURE RANGE (C)	+0 °C to +55 °C
# OF CAN CHANNELS	1
CAN FD	No
CLOCK SYNC	N/A
CASING MATERIAL	PC-ABS
HEIGHT (MM)	N/A
WEIGHT (G)	50.0

Kvaser
Aminogatan 25 A SE 431 53 Mölndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



PRODUCT GROUPS	
RUGGED	No
EMBEDDED SCRIPT	No
MINIMUM BITRATE (KBPS)	5
PC INTERFACE	PCMCIA
ERROR FRAME GENERATION	No
API, FREE	N/A
ON-BOARD TX BUFFER	N/A
STATUS	Obsolete
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
IP CLASS	IP40
ON-BOARD RX BUFFER	N/A

The information herein is subject to change without notice