



Kvaser DRVcan S

EAN: 73-30130-10006-0

A KvaserDRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

A KvaserDRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

-

DRVcan 251 and DRVcan 1050 are for normal, high-speed ISO 11898 CAN bus systems.

-



DRVcan Dnpto is also intended for normal, high-speed ISO 11898 CAN bus systems but is equipped with optocouplers.

-

DRVcan 1053 and DRVcan 1054 are for fault-tolerant CAN buses (sometimes called "low-speed CAN")

-

DRVcan Fi employs **optical fiber** and is used for special applications. Different physical layers are supported through different product versions.

-

DRVcan TnT is used with Truck and Trailers, ISO 11992-1

-

DRVcan S is used with Single-Wire CAN (SAE J2411, GMLAN)

-

DRVlin is used with the LIN bus. Please note that notnote that not all applications listed under Application Support for LAPcan/LAPcan II support the DRVlin.



TECHNICAL DATA - KVASER DRVCAN S

SOUND	No
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
ON-BOARD RX BUFFER	N/A
LENGTH (MM)	500
ERROR FRAME DETECTION	Yes
CONNECTOR	N/A
CIRCUIT BOARD	No
HEIGHT (MM)	N/A
WIDTH (MM)	N/A
CAN FD	No
ON-BOARD BUFFER	No
CASING MATERIAL	PC-ABS
ON-BOARD TX BUFFER	N/A
API, FREE	N/A
INVENTORY	Call Us
CERTIFICATIONS	CE
SILENT MODE	Yes
TIMESTAMP RESOLUTION (US)	N/A
MSGRATE TX MAX	2000
MSGRATE RX MAX	2000
GALVANIC ISOLATION	No
# OF CAN CHANNELS	1
OPERATING TEMPERATURE RANGE (C)	+0 °C to +55 °C
RUGGED	No
API, LICENCED	None
MINIMUM BITRATE (KBPS)	1
IP CLASS	IP40



STATUS	Obsolete
PRODUCT GROUPS	
CURRENT CONSUMPTION	N/A
ERROR FRAME GENERATION	No
NETWORK CHANNEL(S)	
CLOCK SYNC	N/A
EMBEDDED SCRIPT	No
MAXIMUM BITRATE (KBPS)	100
PC INTERFACE	PCMCIA
ERROR COUNTERS READING	Yes
DATABASE DBC SUPPORT	No
WEIGHT (G)	50.0

The information herein is subject to change without notice