



### Kvaser DRVcan Dnopto

EAN: 73-30130-10007-7

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

A Kvaser DRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

- 

DRVcan 251 and DRVcan 1050 are for normal, high-speed ISO 11898 CAN bus systems.

-



DRVcan Dnpto is also intended for normal, high-speed ISO 11898 CAN bus systems but is equipped with optocouplers.

- 

DRVcan 1053 and DRVcan 1054 are for fault-tolerant CAN buses (sometimes called "low-speed CAN")

- 

DRVcan Fi employs **optical fiber** and is used for special applications. Different physical layers are supported through different product versions.

- 

DRVcan TnT is used with Truck and Trailers, ISO 11992-1

- 

DRVcan S is used with Single-Wire CAN (SAE J2411, GMLAN)

- 

DRVlin is used with the LIN bus. Please note that not all applications listed under Application Support for LAPcan/LAPcan II support the DRVlin.



## TECHNICAL DATA - KVASER DRVCAN DNOPTO

CERTIFICATIONS	CE
CURRENT CONSUMPTION	N/A
NETWORK CHANNEL(S)	
MINIMUM BITRATE (KBPS)	5
PC INTERFACE	PCMCIA
SOUND	No
ERROR COUNTERS READING	Yes
INVENTORY	Call Us
CONNECTOR	N/A
PRODUCT GROUPS	
ON-BOARD BUFFER	No
API, LICENCED	None
API, FREE	N/A
TIMESTAMP RESOLUTION (US)	N/A
EMBEDDED SCRIPT	No
STATUS	Obsolete
SILENT MODE	Yes
OPERATING SYSTEM	Win XP,Linux,Win 7,Win Vista,Win 10,Win 8
ERROR FRAME DETECTION	Yes
CIRCUIT BOARD	No
DATABASE DBC SUPPORT	No
MAXIMUM BITRATE (KBPS)	1000
CAN FD	No
# OF CAN CHANNELS	1
LENGTH (MM)	500
CASING MATERIAL	PC-ABS
WEIGHT (G)	50.0



## Kvaser DRVcan Dnopto

WIDTH (MM)	N/A
RUGGED	No
MSGRATE TX MAX	8000
CLOCK SYNC	N/A
MSGRATE RX MAX	10000
ERROR FRAME GENERATION	No
ON-BOARD TX BUFFER	N/A
OPERATING TEMPERATURE RANGE (C)	+0 °C to +55 °C
GALVANIC ISOLATION	Yes
ON-BOARD RX BUFFER	N/A
HEIGHT (MM)	N/A
IP CLASS	IP40

The information herein is subject to change without notice