



Kvaser DRVlin

EAN: 73-30130-10018-3

A KvaserDRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

A KvaserDRVcan is a combined cable, connector and CAN bus driver for the LAPcan / LAPcan II PCMCIA CAN interface. The DRVcans are interchangeable and designed for maximum flexibility and maintainability.

lacktriangle

DRVcan 251 and DRVcan 1050 are for normal, high-speed ISO 11898 CAN bus systems.

lacktriangle

Kvaser
Aminogatan 25 A SE 431 53 Mölndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
https://www.kvaser.com/



DRVcan Dnopto is also intended for normal, high-speed ISO 11898 CAN bus systems but is equipped with optocouplers.

•

DRVcan 1053 and DRVcan 1054 are for fault-tolerant CAN buses (sometimes called "low-speed CAN")

ullet

DRVcan Fi employs **optical fiber** and is used for special applications. Different physical layers are supported through different product versions.

ullet

DRVcan TnT is used with Truck and Trailers, ISO 11992-1

•

DRVcan S is used with Single-Wire CAN (SAE J2411, GMLAN)

•

DRVIin is used with the LIN bus. Please note that notnote that not all applications listed under Application Support for LAPcan/LAPcan II support the DRVIin.



TECHNICAL DATA - KVASER DRVLIN	
ERROR FRAME GENERATION	No
# OF CAN CHANNELS	1
LENGTH (MM)	500
WIDTH (MM)	N/A
MSGRATE RX MAX	8000
PRODUCT GROUPS	
STATUS	Obsolete
CLOCK SYNC	N/A
CASING MATERIAL	PC-ABS
CAN FD	No
MAXIMUM BITRATE (KBPS)	20
RUGGED	No
PC INTERFACE	PCMCIA
INVENTORY	Call Us
SOUND	No
CONNECTOR	N/A
CIRCUIT BOARD	No
GALVANIC ISOLATION	No
ERROR COUNTERS READING	Yes
EMBEDDED SCRIPT	No
WEIGHT (G)	50.0
API, FREE	N/A
ON-BOARD BUFFER	No
OPERATING TEMPERATURE RANGE (C)	+0 °C to +55 °C
SILENT MODE	Yes
ON-BOARD RX BUFFER	N/A
TIMESTAMP RESOLUTION (US)	N/A

Kvaser Aminogatan 25 A SE 431 53 Mölndal SWEDEN Kvaser Europe AB Telephone: +46 31 886344 Email: sales@kvaser.com





OPERATING SYSTEM	Win XP,Linux,Win 7,Win Vista,Win 10,Win 8
IP CLASS	IP40
CERTIFICATIONS	CE
MSGRATE TX MAX	8000
CURRENT CONSUMPTION	N/A
ON-BOARD TX BUFFER	N/A
NETWORK CHANNEL(S)	
ERROR FRAME DETECTION	Yes
MINIMUM BITRATE (KBPS)	1
HEIGHT (MM)	N/A
API, LICENCED	None
DATABASE DBC SUPPORT	No

The information herein is subject to change without notice