



Kvaser Memorator Professional HS/HS

EAN: 73-30130-00351-4

Kvaser Memorator Professional是一款具据功能的USB接口CAN 分析, 品既可以作USB-CAN分析,亦可用作立工作的CAN 据器. Kvaser Memorator Professional更可以与Kvaser LINX合, 支持 J1587.

通的配置, Kvaser Memorator Professional能在境或程 中 , CAN 所有信息. 能有效捕上各异常和突事件, 有助 一步分析.

主要特性 :

- 易快速安
- 使用准USB接口,可作USB-CAN分析使用
- 通道高速CAN接口, 支持速率10 kbit/s~1 Mbit/s
- 建存, 用于存CAN据
- 置4LED, 示工作
- 支持Kvaser Linx 1587
- 模式下, 每秒可20000文
- 支持安模式(silent mode), 不干扰据

Kvaser
Aminogatan 25 A SE 431 53 Mndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



- 支持事件触功能(), 根据外部信或CAN信据定触事件
- 支持据功能
- 支持SD和MMC存卡, 支持容量高16GB
- 能USB接口或者外部取,立工作7V-36V,功耗只有130mA
- 隔离, 保CAN芯片和硬件
- 置用池及

TECHNICAL DATA - KVASER MEMORATOR PROFESSIONAL
HS/HS

WEIGHT (G)	150.0
ON-BOARD TX BUFFER	Yes
TIMESTAMP RESOLUTION (US)	2
MAGISYNC	Yes
SOUND	No
WIDTH (MM)	50
MINIMUM BITRATE (KBPS)	5
MAX CARD SIZE	16
SILENT MODE	Yes
API, FREE	Kvaser API, J2534, RPI210
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
IP CLASS	IP30
PC INTERFACE	USB
# OF CAN CHANNELS	2
INCLUDED CARD SIZE	2GB
CONNECTOR	DSUB 9
DATABASE DBC SUPPORT	Yes
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
MSGRATE TX MAX	20000
CERTIFICATIONS	CE, RoHS
PRODUCT GROUPS	CAN Loggers
CAN FD	No
ERROR FRAME GENERATION	Yes
API, LICENCED	
CASING MATERIAL	PC-ABS
ON-BOARD RX BUFFER	Yes
ERROR COUNTERS READING	Yes



Kvaser Memorator Professional HS/HS

STATUS	Not for new designs
EMBEDDED SCRIPT	No
GALVANIC ISOLATION	Yes
CLOCK SYNC	Yes
MSGRATE RX MAX	20000
NETWORK CHANNEL(S)	2 x CAN HS
ON-BOARD BUFFER	Yes
MAXIMUM BITRATE (KBPS)	1000
RUGGED	No
ERROR FRAME DETECTION	Yes
HEIGHT (MM)	25
CURRENT CONSUMPTION	USB供 (~5V) 130mA • CAN供850mW
CB BOARD	No
LENGTH (MM)	90

The information herein is subject to change without notice